ARMY RESEARCH LABORATORY

Using a Cognitive Architecture to Solve Simultaneous Localization and Mapping (SLAM) Problems

by Troy D. Kelley

ARL-MR-0639   **May 2006**

NOTICES

Disclaimers

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

DESTRUCTION NOTICE—Destroy this report when it is no longer needed. Do not return it to the originator.

Army Research Laboratory

Aberdeen Proving Ground, MD 21005-5425

Using a Cognitive Architecture to Solve Simultaneous Localization and Mapping (SLAM) Problems

Troy D. Kelley
Human Research and Engineering Directorate, ARL

1. REPORT DATE *(DD-MM-YYYY)* May 2006	2. REPORT TYPE Final		3. DATES COVERED (From - To) May 2005
4. TITLE AND SUBTITLE Using a Cognitive Architecture to Solve Simultaneous Localization and Mapping (SLAM) Problems			5a. CONTRACT NUMBER
			5b. GRANT NUMBER
			5c. PROGRAM ELEMENT NUMBER
6. AUTHOR(S) Troy D. Kelley (ARL)			5d. PROJECT NUMBER 62716AH70
			5e. TASK NUMBER
			5f. WORK UNIT NUMBER
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory Human Research and Engineering Directorate Aberdeen Proving Ground, MD 21005-5425			8. PERFORMING ORGANIZATION REPORT NUMBER ARL-MR-0639
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)			10. SPONSOR/MONITOR'S ACRONYM(S)
			11. SPONSOR/MONITOR'S REPORT NUMBER(S)
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			
13. SUPPLEMENTARY NOTES			

14. ABSTRACT

The cognitive production system architecture, the Atomic Components of Thought-Rational (ACT-R), was applied to the problem of simultaneous localization and mapping (SLAM). The map space was represented as a pseudo-topological map of salient features, which was then evaluated with a production system architecture (ACT-R). Results showed that after the robot was placed in five unique locations, it was able to recognize them as spaces that it had previously visited. Results also showed that intrinsic error associated with robotic sensor readings was overcome with the use of the simulated human memory activation equations of ACT-R.

15. SUBJECT TERMS

cognitive modeling; robotics; SLAM

16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON Troy D. Kelley
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified	SAR	18	19b. TELEPHONE NUMBER *(Include area code)* 410-278-5859

Contents

List of Figures

List of Tables

1. Introduction

This report describes the ongoing development of a robotic control architecture called the Symbolic and Subsymbolic Robotic Intelligence Control System (SS-RICS). The system was inspired by computational cognitive architectures from the discipline of cognitive psychology. The idea is that by applying cognitive psychological principles to robotics, perhaps some of the more difficult problems of localization and mapping might be solved.

Cognitive psychologists have made enormous progress in understanding the human mind over the past two decades; moreover, psychologists have had great success in implementing human cognitive theories computationally (*1*). The implementation of human cognitive function in a computational format has allowed cognitive theories to become more bounded, rigorous, and testable. This development has allowed for cognitive theories to be tested on computer systems, including robotic systems. The goal of this research is to show how cognitive psychological principles can be applied to simultaneous localization and mapping (SLAM) problems.

Humans have an inexact sense of space and spatial relationships. Understanding how humans develop a spatial knowledge of the world may help to develop robotic platforms that have an efficient working spatial knowledge of the world. Robots, like humans, have sensors that render an inexact representation of the world. Thus, any representational mechanism of spatial knowledge implemented on a robot must support incomplete and error-prone data, or what one psychological researcher calls "states of partial knowledge" (*2*). The conclusion from many psychologists is that humans use minimal spatial representations and try to maximize the benefit from such a paucity of spatial representation.

One classic example of using minimal representations of spatial maps is from an experiment done by Stevens and Coupe (*3*). In the study, students at the University of San Diego in California were asked to estimate the direction of their city from Reno, Nevada. Most students estimated the direction as northeast, when in fact, Reno is northwest of San Diego. The authors hypothesized that the participants' estimates were influenced by the fact that Nevada is basically due east of California. Other studies have found similar results. Studies have shown that North Americans tend to locate European cities south of North America when they are of similar latitudes (*4*). Thus, it would seem that participants had a general hierarchical cognitive representation of the United States that is generally minimalist, and from this, they generalized their decisions about individual points within the United States.

The robotics community has devoted an inordinate amount of time and computational power to creating exact Euclidian maps of environments, when it is not clear that this is absolutely necessary for efficient navigation through the world. Research from cognitive psychology tells us that general maps of topological relationships are more efficient and robust. There have been

some recent papers in the robotics community showing promise for solving the SLAM problem without using explicit localization (*5*). The SLAM problem involves defining locations and possible locations for the robot to navigate to without using a predefined map. We feel that a non-explicit representation for robot localization is the most promising direction for future research.

2. Method

For this research, a Pioneer P3-DX robot from ActivMedia Robotics was used. The robot had an on-board computer system running the Linus Torvald's UNIX[1] version 7.3 operating system. The robot was equipped with the ARIA (Advanced Robotic Interface for Applications) development environment which is a collection of C++ libraries developed by ActivMedia for robotic control. The robot was equipped with SONAR (sound navigation and ranging), a SICK[2] laser system and a Canon VC-C4 camera. During the early stages of knowledge generation for this study, a real-world area with real obstacles was used. For the second part of the study, when the specific interest was localization, the simulated robot software provided by ActivMedia was used. The ActivMedia simulator software also simulates error associated with robot movement and localization.

3. Procedure

For the knowledge development phase, a robotic test bed was developed in order to allow the robot to explore a small world in real time. The test bed included boxes and obstacles which were positioned in a room to allow the robot to navigate in a fairly complex world. This world was also duplicated in the simulated environment for the localization phase.

3.1 Background

The SS-RICS was greatly inspired by recent developments in cognitive psychology, especially computational models of cognition, primarily ACT-R (Adaptive Control of Thought – Rational). The SS-RICS is an all-encompassing architecture, (i.e., it includes most major aspects of human cognitive functioning). The architecture includes an ACT-R-like production system, as well as lower structures that mimic human problem-solving behavior. The architecture does not at this time include emotional behavior or metacognitive behavior.

---

[1]UNIX is a registered trademark of Lucent Technologies, Bell Labs Innovations.
[2]Not an acronym

ACT-R is considered a production system architecture. Production system architectures have been used successfully to mimic human behavior (*1*) and the production system is the basis of ACT-R, as well as other cognitive architectures including Soar (*6*). A production system uses a deductive reasoning system that uses relatively simple "if-then" type rules to reach conclusions. The SS-RICS uses the production system as a rule-based problem-solving system. For example, if an action is to determine the identity of a scene, a production system with a specific set of localization rules will be loaded into the SS-RICS and used for localization.

ACT-R was developed through a long history of psychological research, especially in the area of human memory. The SS-RICS uses algorithms developed to mimic human memory. In SS-RICS, the strength of memory items is a power function and was based on the activation function developed in ACT-R (*1*) (figure 1). However, within the SS-RICS, a function was added to allow the activation levels to return to zero (RTZ); this is different from the activation equations developed by Anderson and Lebiere (*1*). By adding an RTZ, this allows the simulation of a refractory period normally exhibited by neurons.

Figure 1. Activation values decreasing, increasing and returning to zero.

3.2 Knowledge Development

Our robot was capable of detecting "points" using its SICK laser system. These points are planar points (i.e., points on one continuous plane) that the robot can use to detect the approximate distance to objects in the world. Our first phase of perceptual processing for the robot was called the "neuron level." (Note, while this is called the neuron layer, it is NOT a neural network.) The neuron level uses algorithms to immediately start looking for points in the world which might be grouped together as lines. The overall architecture then attaches an activation value to areas in the robot's SICK laser perception which correspond to areas where possible lines have been detected (figure 2).

The two graphs in figure 2 showing the robot visual field should be examined together. The top graph shows the robot visual field in degrees and the bottom graph shows the activation value to the corresponding visual field. As shown, activation increases in areas where there is a continuous line representation and decreases in areas where the line representation is not as continuous. This gives the robot a "sense" of where lines are in its SICK laser perceptual field. More importantly, this mimics systems within the human perceptual system at the neuron level by highly activating or strengthening the activity of cells that correspond to important items in the perceptual field.

Figure 2. Robotic visual angle in degrees and activation values associated with line objects.

In some ways, the problems of object recognition and the problems of SLAM are intimately tied together. For example, people frequently use object identification as a basis for navigation through the world, (i.e., go to the church, turn left, then go to the large oak tree, and turn right). So, before addressing problems of SLAM, the robot needed a basic understanding of objects in the world before it could determine where in the world it was at any given time.

In order to allow the robot to navigate through its own environment, the SS-RICS was developed to allow for goal-directed behavior. Cognitive psychologists have shown that much of human behavior is primarily goal directed (*7*). Goals for human beings can include goals to achieve success, goals to procreate, or goals to satiate hunger. Goals in the SS-RICS architecture may include goals to avoid objects, goals to examine objects, or goals to acquire new information. Goal-directed behavior is not simply the execution of one goal or another but rather a set of conflicting goals that allow complex behavior to emerge from their dynamic interaction. New goals may be added as behavior matures or develops. Conflicting goals also compete for behavioral control, depending on the activation strength of each goal, and internal or external stimuli can change the activation strengths of each goal.

For SS-RICS, goals were developed that were similar to goals that one would expect to see in an intelligent human infant. The main goal was to explore the world; this also included subgoals of avoiding objects and creating memories of the world. Next, the robot gradually developed a goal to ask questions about the world. While the robot was wandering around the room, it periodically asked questions about lines that it had detected. For example, if the robot was interested in a certain line that its neuron layer had identified as important or salient, the robot would ask, "what is this thing at degree -90 to -69?," to which the operator would answer, "it is a line." This was then added to the production system as the symbolic representation (LINE) for what the robot was perceiving at the time it encountered the line. Later in the interaction, the robot may develop another goal to know how the operator knows what constitutes a line or the rules for a line. The user would then enter into the robot what the rules are for a line (lines have end points and start points). This again is added to the production system as rules that constitute a line.

The human-robotic interaction was necessary for the localization behavior, in that it served as a building block for the symbolic representation of the world. Additionally, this interaction simulated how humans learn symbolic rules for objects in the world. It is similar to a child asking "why" over and over. Answers from parents to children's "why" questions frequently include rules. In this case, the robot was motivated by a goal to ask what a line was from its own perceptual experience. It then learned the symbolic representation of a line from its interaction with an operator. It was then able to use the rules that it learned to help determine what objects are in the world, and subsequently, where it was in the world.

3.3   Localization

The robot was implemented to develop topological maps that the production system (ACT-R) was capable of loading and analyzing. For example, once the robot was able to identify "lines," it then grouped lines together as scenes. So, in addition to asking questions about objects in the world, the robot gradually developed a goal to store scenes or specific locations of the world. The robot did this by asking "where am I" to which the operator replied "front right of room."

The robot learned five locations of a room that were entered into the ACT-R production system. An approximate layout of the room with each of the five locations is shown in figure 3. A

sample set of what was generated for the production system is show in table 1. (Note: the line numbers are arbitrary.)


Figure 3. Approximate layout of room and five locations
the robot was to learn.

Table 1. Five scene locations, in rule based format, first scan.

Location 1	Location 2	Location 3	Location 4	Location 5
(near-left line5)	(far-left line8)	(near line3)	(center line7)	(center line7)
(near-right line1)	(left line4)	(near-left line4)	(left line8)	(left line11)
(near-right line2)	(left line5)	(near-left line5)	(near-left line9)	(near-left line10)
(near-right line3)	(left line7)	(near-right line1)	(near-right line2)	(near-left line8)
(near-right line4)	(near line3)	(near-right line2)	(near-right line4)	(near-left line9)
	(near-left line6)		(near-right line5)	(near-right line4)
	(near-right line1)		(near-right line6)	(near-right line5)
	(near-right line2)		(right line1)	(right line1)
			(right line3)	(right line2)
				(right line3)
				(right line6)

As can be seen from the table 1, the production system included only one type of object, a line. Next, the robot was able to encode the general location of the line (i.e., near, far, left, center or right (which are based on threshold values)). This was the only information about each one of the five locations. Next, the robot was placed into approximately the same locations by a human operator in the robotic simulator. The operator only had a rough map of the general locations as shown in figure 3. This new placement generated a new set of five locations. Those locations are listed in table 2. Once the robot was placed in each location the second time, using the ACT-R production system, the robot was able to identify each of the five locations. So, by using only line information and general information about the location of each line (i.e., near-left) the robot was able to determine its locations for five different scenes.

Table 2. Five scene locations, rule based format, second scan.

Location 1	Location 2	Location 3	Location 4	Location 5
(near line6)	(far-left line11)	(near line3)	(center line5)	(center line6)
(near-left line7)	(left line10)	(near-left line4)	(left line6)	(left line11)
(near-right line1)	(left line6)	(near-left line5)	(near-left line7)	(near-left line10)
(near-right line2)	(left line7)	(near-right line1)	(near-right line2)	(near-left line7)
(near-right line3)	(near-left line8)	(near-right line2)	(near-right line4)	(near-left line8)
(near-right line4)	(near-left line9)		(right line1)	(near-left line9)
(near-right line5)	(near-right line1)		(right line3)	(near-right line2)
	(near-right line2)			(near-right line3)
	(near-right line3)			(near-right line4)
	(near-right line4)			(right line1)
	(right line5)			(right line5)

As can be seen from table 3, because of the inherent error in sensor readings, each scan from the same location is slightly different. The near-left line occasionally switches to a near line and then back to a near-left line.

Table 3. Four scans of location 1.

Scan 1	Scan 2	Scan 3	Scan 4
(near-left line5)	(near line5)	(near-left line5)	(near line5)
(near-right line1)	(near-left line6)	(near-right line1)	(near-left line6)
(near-right line2)	(near-right line1)	(near-right line2)	(near-right line1)
(near-right line3)	(near-right line2)	(near-right line3)	(near-right line2)
(near-right line4)	(near-right line3)	(near-right line4)	(near-right line3)
	(near-right line4)		(near-right line4)

By using the activation values within ACT-R, this helped to reduce the effects of the error associated with each scan. First, ACT-R groups the lines of similar types together (i.e., near right), then does a comparison of each scan and does a match with existing scans that it has in its memory. Scans that match existing memories receive higher activation values. The logic here is that the more common a scan is, the more likely the scan reflects reality, since the error scans occur less frequently. As can be seen from figure 4, after three ACT-R cycles of matching three groups of lines, ACT-R has determined that the near-right group is the most stable and matches the best to the previous location scans (note, not all the scans used in the ACT-R analysis are included in table 3). Next, the near-left group is slightly less active, primarily because it occurs less often (only one instance in each group, while the near-right group line instance occurs four times in its group).   ACT-R has concluded that since it is less active, it is considered less stable and less a representation of true reality. Finally, the near group (which is actually not a group because it is only one line, but the word "group" here is used for consistency since it is treated the same as the other groups of lines within ACT-R) is the least active. This activation level is because it does not occur at all in scans 1 and 3 and occurs only once in instances 2 and 4. This instance would be considered an error and would be grounds for ignoring or removal in future calculations of localization within ACT-R.

Another note about the psychological plausibility of this analysis: With the SS-RICS architecture and by using ACT-R, meaningful representations have been grouped together (line groups). For example, with the scene analysis, the representation starts with points, then progresses to lines, then progresses to groups of lines. (ACT-R allows manipulation of the near-left group of lines shown in the graph as one memory object, so it can be thought of as a single representation.) This is very similar to human memory and gestalt-type knowledge organization.


Figure 4. Line group activation values for three groups of lines.

3.4 Summary

Using this simple representation, the robot creates general representations of specific locations. By using general representations, we hope that the overall representation is more robust and less prone to failure. Furthermore, this representation should not be affected by increased scaling, which has caused problems for traditional SLAM techniques. The error in this representation does not necessarily increase with the size of the map.

In our study, the five scenes were arbitrary locations on the map. However, ideally, the scenes should be considered "landmarks" or important and salient features of the environment. For example, passing through a doorway, rounding the corner of a hallway, or entering a stairwell would be the kinds of important and salient landmarks that the robot would store in its memory. Ideally, the robot would learn from trial and error navigation that certain salient features of the environment are important for navigation and localization. However, in this case, we have hard coded this information.

Typically, there should be no need for any representation between the landmarks. The robot only needs to know that it is located at one landmark and perhaps is moving to another landmark. The only representation it might have is that it is "between" landmarks. If an interruption signaled the need to move to a new landmark, then a new landmark could be created at the spot of the interruption which might be between two landmarks. The location of the interruption would create an important event, which would generate the need for a new landmark. However, this would be one of the rare instances when a representation between landmarks would be needed.

4.   Conclusions

SS-RICS represents the ongoing development of a robotic control architecture that is based heavily on the principles of cognitive psychology. This architecture gave our robot the ability to explore a space in much the same way a human infant would explore a space. By developing a neuron layer similar to the human neuron layer, the robot was attracted to certain salient features of its environment. By examining salient objects and asking the operator questions about salient objects, the robot was then able to develop a symbolic representation of the space and use that representation for localization procedures. The robot was able to correctly identify five similar locations in a simulated environment. The robot was also capable of chunking together representations: first for points, then lines, and then groups of lines and was able to organize groups of lines into a coherent knowledge set. Activation values (developed from human memory decay algorithms) were used to reduce the influence of noise on our localization procedures. Also, note that the robot was able to recognize similar spaces by using a small amount of representations (i.e., lines and locations of lines). It is encouraging to see that just a small amount of representation can go a long way to identifying locations in a space.

Further research will be done to move this simulation into the real world to see if the robot is capable of performing the same tasks in the real world as in the simulation. Additionally, a task will be to give the robot a more detailed representations (edges, corners) and more information about movement (global X,Y locations) in order to further improve the topological localization strategies.

5. References

1. Anderson, J. R.; Lebiere, C. *The Atomic Components of Thought*. Lawrence Erlbaum Associates: Mahwah, NJ, 1998.

2. Kuipers. B. J. The "Map in the Head" Metaphor. *Environment and Behavior* **1982**, *14*, 202–220.

3. Stevens, A.; Coupe, P. Distortions in Judged Spatial Relations. *Cognitive Psychology* **1978**, *10*, 422-437.

4. Tversky, B. Distortions in Memory for Maps, *Cognitive Psychology* **1981**, *13*, 407-433.

5. Choset, H.; Nagatani, K. Topological Simultaneous Localization and Mapping (SLAM): Toward Exact Localization without Explicit Localization. *IEEE Transactions on Robotics and Automation* **April 2001**, *17* (2).

6. Newell, A. *Soar: A Cognitive Architecture in Perspective*, Kluwer Academic. Harvard University Press: Cambridge, MA, 1990.

7. Frese, M.; Sabini, J. (eds) *Goal-Directed Behavior. Goal-Directed Behavior: The Concept of Action in Psychology*. Erlbaum: Hillsdale, NJ, 1985.

8. Koffka, K. *Principles of Gestalt Psychology*. Routledge, London, 2001.

1
(PDF
ONLY)
DEFENSE TECHNICAL
INFORMATION CTR
DTIC OCA
8725 JOHN J KINGMAN RD
STE 0944
FORT BELVOIR VA 22060-6218

1   US ARMY RSRCH DEV & ENGRG CMD
SYSTEMS OF SYSTEMS
INTEGRATION
AMSRD SS T
6000 6TH ST STE 100
FORT BELVOIR VA 22060-5608

1   INST FOR ADVNCD TCHNLGY
THE UNIV OF TEXAS AT AUSTIN
3925 W BRAKER LN STE 400
AUSTIN TX 78759-5316

1   DIRECTOR
US ARMY RESEARCH LAB
IMNE ALC IMS
2800 POWDER MILL RD
ADELPHI MD 20783-1197

1   DIRECTOR
US ARMY RESEARCH LAB
AMSRD ARL CI OK TL
2800 POWDER MILL RD
ADELPHI MD 20783-1197

2   DIRECTOR
US ARMY RESEARCH LAB
AMSRD ARL CS OK T
2800 POWDER MILL RD
ADELPHI MD 20783-1197

1   ARMY RSCH LABORATORY - HRED
ATTN AMSRD ARL HR M   DR M STRUB
6359 WALKER LANE SUITE 100
ALEXANDRIA VA 22310

1   ARMY RSCH LABORATORY - HRED
ATTN AMSRD ARL HR MA   J MARTIN
MYER CENTER RM 2D311
FT MONMOUTH   NJ 07703-5630

1   ARMY RSCH LABORATORY - HRED
ATTN AMSRD ARL HR MC   A DAVISON
320 MANSCEN LOOP STE 166
FT LEONARD WOOD MO 65473-8929

1   ARMY RSCH LABORATORY - HRED
ATTN AMSRD ARL HR MD   T COOK
BLDG 5400 RM C242
REDSTONE ARSENAL AL   35898-7290

1   COMMANDANT USAADASCH
ATTN ATSA CD
ATTN AMSRD ARL HR ME MS A MARES
5800 CARTER RD
FT BLISS TX 79916-3802

1   ARMY RSCH LABORATORY - HRED
ATTN AMSRD ARL HR MI J MINNINGER
BLDG 5400 RM C242
REDSTONE ARSENAL AL   35898-7290

1   ARMY RSCH LABORATORY - HRED
ATTN AMSRD ARL HR MM DR V RICE
BLDG 4011 RM 217
1750 GREELEY RD
FT SAM HOUSTON TX 78234-5094

1   ARMY RSCH LABORATORY - HRED
ATTN AMSRD ARL HR MG R SPINE
BUILDING 333
PICATINNY ARSENAL NJ   07806-5000

1   ARL HRED ARMC FLD ELMT
ATTN AMSRD ARL HR MH C BURNS
BLDG 1467B ROOM 336
THIRD AVENUE
FT KNOX KY 40121

1   ARMY RSCH LABORATORY - HRED
AVNC FIELD ELEMENT
ATTN AMSRD ARL HR MJ D DURBIN
BLDG 4506 (DCD) RM 107
FT RUCKER AL 36362-5000

1   ARMY RSCH LABORATORY - HRED
ATTN AMSRD ARL HR MK MR J REINHART
10125 KINGMAN RD
FT BELVOIR VA 22060-5828

1   ARMY RSCH LABORATORY - HRED
ATTN AMSRD ARL HR MV HQ USAOTC
S MIDDLEBROOKS
91012 STATION AVE ROOM 111
FT HOOD TX   76544-5073

1   ARMY RSCH LABORATORY - HRED
ATTN AMSRD ARL HR MY M BARNES
2520 HEALY AVE STE 1172 BLDG 51005
FT HUACHUCA AZ 85613-7069

1	ARMY RSCH LABORATORY - HRED ATTN AMSRD ARL HR MP D UNGVARSKY BATTLE CMD BATTLE LAB 415 SHERMAN AVE UNIT 3 FT LEAVENWORTH KS 66027-2326
1	ARMY RSCH LABORATORY - HRED ATTN AMSRD ARL HR MJK J HANSBERGER JFCOM JOINT EXPERIMENTATION J9 JOINT FUTURES LAB 115 LAKEVIEW PARKWAY SUITE B SUFFOLK VA 23435
1	ARMY RSCH LABORATORY - HRED ATTN AMSRD ARL HR MQ M R FLETCHER US ARMY SBCCOM NATICK SOLDIER CTR AMSRD NSC SS E BLDG 3 RM 341 NATICK MA 01760-5020
1	ARMY RSCH LABORATORY - HRED ATTN AMSRD ARL HR MY DR J CHEN 12423 RESEARCH PARKWAY ORLANDO FL 32826
1	ARMY RSCH LABORATORY - HRED ATTN AMSRD ARL HR MS MR C MANASCO SIGNAL TOWERS RM 303A FORT GORDON GA 30905-5233
1	ARMY RSCH LABORATORY - HRED ATTN AMSRD ARL HR MU M SINGAPORE 6501 E 11 MILE RD MAIL STOP 284 BLDG 200A 2ND FL RM 2104 WARREN MI 48397-5000
1	ARMY RSCH LABORATORY - HRED ATTN AMSRD ARL HR MF MR C HERNANDEZ BLDG 3040 RM 220 FORT SILL OK 73503-5600
1	ARMY RSCH LABORATORY - HRED ATTN AMSRD ARL HR MW E REDDEN BLDG 4 ROOM 332 FT BENNING GA 31905-5400
1	ARMY RSCH LABORATORY - HRED ATTN AMSRD ARL HR MN R SPENCER DCSFDI HF HQ USASOC BLDG E2929 FORT BRAGG NC 28310-5000
1	ARMY G1 ATTN DAPE MR B KNAPP 300 ARMY PENTAGON ROOM 2C489 WASHINGTON DC 20310-0300

ABERDEEN PROVING GROUND

1	DIRECTOR US ARMY RSCH LABORATORY ATTN AMSRD ARL CI OK (TECH LIB) BLDG 4600
1	DIRECTOR US ARMY RSCH LABORATORY ATTN AMSRD ARL CI OK TP S FOPPIANO BLDG 459
1	DIRECTOR US ARMY RSCH LABORATORY ATTN AMSRD ARL HR MR F PARAGALLO BLDG 459
5	DIRECTOR US ARMY RSCH LABORATORY ATTN AMSRD ARL HR SE T KELLEY BLDG 459